



HD-CVI / TVI / AHD Passive Video Balun



IV-HD2VB



IV-HD2VBPT (with Pigtail)

Features:

- . Supports CVI / TVI / AHD
- . Passive Balun -Recommended to use **Shielded Twisted Pair (STP)**
- . Up to 1350 feet (450 M) for 720P CVI Cameras
- . Up to 750 feet (250 M) for 1080P CVI Cameras
- . Up to 750 feet (250 M) for 720P/1080P TVI Cameras
- . Up to 960 feet (320 M) for 720P AHD cameras
- . Built-in transient suppression protection

Specification		IV-HD2VB / IV-HD2VBPT
Frequency Response		DC to 60MHz
Attenuation		0.5dB typ
CMRR		60 dB
Surge protection		4KV
ESD		8KV
Connectors		Male BNC and "Press-Fit" terminal blocks
Impedance	Male BNC	75 ohms
	Terminal	100 ohms
Working Temperature		14 °F ~ 122 °F / -10°C to +50°C
Storage Temperature		-22 °F ~ 158 °F / -30°C to +70°C
Humidity		0 to 95%
Wire Type		UTP5
Materials		ABS Plastic
Dimension		1.54" x 0.67" x 0.75" / 39mm*17mm*19mm (excluding connectors)
Weight		52g/pair

