






## 4 in 1 1080P Autofocus Indoor / Outdoor IR Dome

### IV-DVFH6100IRW-F-H-AF

#### Features:

- . 1080P@TVI/CVI/AHD/CVBS video output
- . 1/3" Progressive Sensor
- . IR LED: 36pcs
- . IR distance: 100-115 ft
- . Lens: 2.8-12mm, Autofocus / 4X zoom
- . Ultra low illumination
- . DC 12V IP66
- . Up the Coax (via coaxial cable)
- . Motion detection, Privacy mask, HLC, WDR



#### Use the OSD joystick to switch among the four video output modes:

- \* Push the joystick "UP" button key over 5 seconds to CVI mode
- \* Push the joystick "DOWN" button key over 5 seconds to TVI mode
- \* Push the joystick "LEFT" button key over 5 seconds to CVBS (Analog 960H) mode
- \* Push the joystick "RIGHT" button key over 5 seconds to AHD mode
- \*\* Each Boot up allows one video mode selection.

if you need to switch to another mode, you will need to reboot again.

Specification	IV-DVFH6100IRW-F-H-AF
Horizontal Resolution	1080P@ TVI/CVI/AHD/CVBS
Image Sensor	1/3" Progressive Sensor
Signal System	PAL / NTSC
S/N Ratio	More than 52 dB
Lens	2.8-12mm Autofocus / 4 X zoom
Electronic Shutter	AUTO/MANUAL /FLICKER
Min. Illumination	0.001Lux (F1.2), Black and White (0 Lux LED on)
Back Light	Off / HLC / BLC / WDR
DNR	Off / Low / Mid / High
Day / Night	EX / Auto / Color / B & W
AGC	0-20 steps
Sens up	Off / 2x-8x
White Balance	Auto/Auto-ext/Preset/Manual
Digital Zoom	1.0x-8.0x
Privacy Mask	Off / 0~15 Zones
LED Wave Length	36pcs 850nm Infrared LED
IR Distance	100-115 ft
Connector Video	BNC
OSD Menu	Yes (via DVR PTZ Control)
LED Switch	AUTO
IP Rating	IP66
Video Output	TVI / CVI / AHD / CVBS
Signal Transmitting	Over 1050 feet distance via Coaxial cables(RG59 75-3 Full Cooper)
Dimension	Ø 4.75" X 3.75" (h)
Weight	1.65 lbs.
Storage Temperature	-4 °F ~ 140 °F
Operation Temperature	-4 °F ~ 122 °F
Power Supply	DC 12V ±10%