



## 25CH Ultra 5-in-1 DVR (SDI/AHD/TVI/960H/IP)

### IV-8725-RXHD



#### Features:

- . H.265 Video Compression
- . 4K Live View
- . Support TVI & AHD up to 3 Megapixel Video Input
- . HD-SDI: 1080P @ 30/25 fps, TVI: 1080P @ 30/25 fps, AHD: 1080P @ 30/25 fps  
960H /D1, H.264 / H.265 IP CAM
- . Support OSD setting over coaxial (UTC)
- . Support HD-SDI Video Input
- . Support IP camera with Onvif Profile protocol (V2.4)
- . Cross device function for redundant recording
- . Ideal for project bid, public place like airport, bank, and administration



Specification		IV-8725-RXHD
	Camera Input	25 (16 BNC + 9 IP)
Video	Input	HD-SDI: 1080P @ 30/25 fps
		TVI: 1080P @ 30/25 fps
		AHD: 1080P @ 30/25 fps
		960H / D1; H.264 / H.265 IP CAM
	Output	Max. 3840x2160
		1 HDMI with Audio and 1 VGA ( Max. 1920x1080)
Audio	Input	8 RCA
	Output	2 RCA
System	Operating System	Embedded Linux OS
	SATA Devices	Supports Max. x 7 SATA Devices (HDDx6+eSATAx1, HDDx4+Optical Devicex1+eSATAx1)
	External HDD	YES ( eSATA )
	Sensor In (NO, NC)	Alarm-in x 16
	Relay out	Relay-out x 4
	Serial Interface	RS-485 x 2
	USB	USB 3.0 x1, USB2.0 X2
	Dimension ( mm )	442(w)x92(h)x438(d)
	Weight (w/o HDD )	5.3 KG / 11.68 lbs
	Power Rating	AC 110/220V 250W
Display	Split screen	1, 4, 9, 13, 16, 25, SEQ.
	Auto Channel Switching	Switching time : 1 ~ 99 sec
	Mode	Zoom, Auto SEQ.
Recording	Compression	H.265 / H.264 High Profile
	Main (Recording)Resolution	1920 x 1080, 1280 x 720; 944 x 480 ,704 x 480, 352 x 240 (NTSC) / 944 x 576 ,704 x 576, 352 x 288 (PAL)
	Sub (Network)Resolution	640 x 360 / 352 x 240, 176 x 120 ( NTSC) / 352 x 288, 176 x 144 (PAL)
	Picture Quality	10~100 levels for adjustment
	Mode	Continuous, Event, Schedule
	Record Rate	NTSC 1080p 480fps; 720p 480 fps / PAL 1080p 400fps ; 720p 400 fps
	Pre-Alarm	1 ~ 3 SEC
	Post-Alarm	1 ~ 100 SEC
Playback	Search mode	Date/time, Event
	Zoom	Digital (x2~ x5)
Network	Network Interface	10/100/1000 Ethernet
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS
	Application	Windows 7 , 8, 8.1, 10 Mac OS X
	Remote Software	SoCatch App, IE Browser, iCMS Pro
	Account	1 Admin + 10 Users
	Mobile Device	iPhone, iPad, Android
Backup	Interface	USB 2.0 or SATA
	Audio Backup	YES
	Backup Type	Network, Ext. USB flash device , SATA optical DVD..etc
Alarm	Motion Detection	Sensitivity: 100 levels for each channel Area: Programmable individually
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
OSD & DVR Control	Multi-Language	Supported
	Camera Title	Multi-Language
	USB Mouse	YES
	Touch Panel	Touch Panel LCD Monitor
	Remote Controller	(USB Interface, EETI Chipset Only)
	System Upgrade	IR Remote Control
	Pan/Tilt/Zoom	USB Flash Drive, iWatch DVR
General	Control	Control From RS485 Interface
	Operating	( Pelco P, Pelco D, Samsung, LG, LiLin )
	Temperature	-10°C ~ +55°C (14°F ~ 131°F)
	Operating Humidity	10%~80%