



2 Megapixel IR Bullet Camera

IV-BU28122MP

Features:

- . 1/2.8" 2 Megapixel Sony Exmor Sensor
- . H.264/ JPEG dual-stream
- . 1920x1080 / 30 fps
- . True Day / Night with ICR Filter
- . 2.8-12mm varifocal lens
- . Built-in 1/1 audio in/out
- . Max. IR LEDs length 105 feet
- . IP66, PoE



Specification		IV-BU28122MP
Camera	Image Sensor	1/2.8" 2 Megapixel Sony Exmor Sensor
	Effective Pixels	1920(H)x1080(V) / 30 fps
	Electronic Shutter Speed	Auto / User, 1/5~1/50,000; 50/60Hz software selectable
	Min. Illumination	Color: 0.1 Lux/F1.2 (0 Lux IR LED on)
	Video Output	Service BNC output dangle cable with IP OSD from screw fit panel
	Lens	2.8~12mm vari-focal IR Corrected
Parameters	IR LEDs	15pc Super Flux IR LED 850nm for 105 feet
	Day/Night	True Day/Night with ICR Filter
	Compensation	H.264 High profile (support baseline profile) / MJPEG
	Bit Rate (CBR / VBR)	Stream 1: 50Kbps-12Mbps; Stream 2: 10Kbps-6Mbps; Stream 3: (Fixed)
	Quality Setting	1 - 9 (9 Highest)
	Multi-Streaming	User setting of Stream 1/2 at supported resolutions, Stream 3 MJPEG Stream
	Brightness / Sharpness	Variable 0~100 / 0~100
	Gain Control	Auto / Fixed 8~102db
	Orientation	Horizontal Mirror / Vertical Flip
	Text Overlay	Time / Date / Camera / Custom OSD
Network	Masking	5 User defined masking areas < 8% of total picture
	Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
	TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
	Compliance	Onvif v2.2 Profile-S Listed
	RTSP Video	Standard RFC2326, Support Quick Time / VLC Player. User security authentication (Enabled/Disabled)
	Web Language	English, Chinese, Russian, Polish
	Recording Simultaneous	Local Micro SD Memory, Remote FTP Server, TCP/UDP CMS, RTSP connection (stream 1, 2, or 3)
	Network Protocols	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP. Unicast and Multicast supported
Audio	Memory Card Slot	Internal memory card supports Max 64GB. Supports Edge Recording
	Input / Output	1 x RCA Input / 1 x RCA Output @ 1v Line Level
General	Audio Compression	G711 A-Law, G711 U-Law, RAW-PCM
	Power	DC12V, @ 560mA (IR LED On) / PoE Class 3
	Temperature	Operating: 14°F~131°F. Storage: -4°F~140°F
	Operating Humidity	10%~85% RH
	Approvals	CE / FCC / RoHS Compliant / IP66 / IK5
Dimensions	102.5" x 2.75"	