



2 Megapixel IR Bullet Camera

IV-BUF362MP

Features:

- . 1/3" Sony Exmor
- . HD 1080P
- . 0.1Lux @(F1.4,AGC ON), 0Lux with IR
- . H.264 high profile compression
- . IR-CUT filter switch
- . Dual stream, 3-Axis
- . Built in PoE, ONVIF 2.0



Specification	IV-BUF362MP
Camera	
Image Sensor	1/3" Sony Exmor
Effective Pixels	1920 x 1080
Scanning System	Progressive
Min. Illumination	Color:0.1Lux /F1.4 B/W:0.01 Lux / F1.4, 0 Lux (IR on)
Electronic Shutter	Auto/ Manual 1/50 ~ 1/10,000
Day & Night	Auto (ICR) / Color / B/W
S/N Ratio	> 50dB
Backlight Compensation	BLC
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 Areas
IR distance	45~60 ft
Slow Shutter	None /Low/ Middle/ High
Motion Detection	22X18 area
Lens	
Focal Lens	3.6mm
Max Aperture	F2.0
Mount Type	Board-in Type
Video	
Compression	H.264 Main Profile, JPEG Snapshot
Resolution	50Hz Mode:1080P(1920x1080) / 720P(1280x720) / D1(704X576) / 60Hz Mode: 1080P(1920x1080) / 720P(1280x720) / D1(704X480) /
Frame Rate	Main Stream: 1920x1080 (1 ~ 25/30fps), Sub Stream: 704x576 (1 ~ 25/30fps)
Bite Rate	H.264: 64K~4096Kbps
Network	
Ethernet	RJ-45 (10/100 Base-T)
Protocols	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud
ONVIF	ONVIF Ver. 2.0
Max. User Access	5 users
Smart Phone	iPhone,Windows Mobile, BlackBerry,Symbian, Android
Browser	IE、Chrome、Firefox、Safari
General	
Operating Condition	-14 °F ~ 122 °F (-25°C~+50°C), Humidity10%~ 90%
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<10W
Protection Range	IP66
Dimension	6.28" x 2.93"
Weight	1.15 lbs (0.52Kg)