



Outdoor IR Bullet Camera

IV-BV742-U



Features:

- . 1/3" SONY Effio-E, 700TVL
- . Dual power with OSD
- . Lens:2.8-12mm varifocal Lens
External focus & zoom
- . IR LED: 42pcs LED
- . IR distance: 105~120 ft
- . Vandalproof metal case
- . With CCTV tester connector & LED level adjuster & OSD Menu button
- . With 3-Axis cable protected bracket
- . IP66



IV-OSD Remote Controller

(Optional)



SPECIFICATION	IV-BV742-U
Horizontal Resolution	700TVL
Image Sensor	1/3" SONY Effio-E
Signal System	PAL/NTSC
Pixels	PAL:976H X 582V
	NTSC:976H X 494V
Lens	2.8-12mm vari-focal lens, external focus & Zoom
Electronic Shutter	1/50 (1/60)~1/100,000sec
Min.Illumination	0.01Lux(F1.2),Black and White (0Lux LED on)
BLC	BLC (9 Zone is adjustable) /HLC/OFF
AGC	High/low (5dB-62.8dB)
White Balance	ATW/PUSH/Manual/Hold/Fixed gain/Color rolling suppression
LED Wave Length	42pcs 850 nm Infrared LED
IR Distance	105~120 ft
OSD menu	Operation
LED Auto Switch	Auto
IP Rating	IP66
Video Output	VBC: 1.0Vp-p;75Ω BNC
Dimension	4.80"X2.75"X2.75"
Weight	2.25 lbs.
Storage Temperature	-4 °F~140 °F
Operating Temperature	-40°F~140°F
Power Supply	DC 12V, AC 24V