



1.3 Megapixel Mini Dome Camera

IV-DEF3613MP

Features:

- . 1/3" Aptina CMOS
- . HD 720P
- . 0.1Lux / F1.4 (0 Lux with IR)
- . H.264 high profile / JPEG Snapshot
- . IR-CUT filter switch
- . Dual stream, 3-Axis
- . Built in PoE
- . ONVIF 2.0



Specification		IV-DEF3613MP
Camera	Image Sensor	1/3" 1.3 Megapixel Aptina CMOS
	Effective Pixels	1280 x 960
	Scanning System	Progressive
	Min. Illumination	Color:0.1Lux / F1.4, B/W: 0.01 Lux / F1.4,0 LUX (IR on)
	Electronic Shutter	Auto / Manual 1/50 - 1/10,000
	Day & Night	Auto (ICR) / Color / B/W
	S/N Ratio	> 50dB
	IR distance	60 feet
	Backlight Compensation	BLC
	White Balance	Auto
	Gain Control	Auto / Manual
	Noise Reduction	3D
	Privacy Masking	Up to 4 Areas
	Slow Shutter	None /Low/ Middle/ High
Motion Detection	22X18 area	
Lens	Focal Lens	3.6mm / F1.2 / Angle of View H:70°
	Mount Type	Board-in Type
Video	Compression	H.264 Main Profile, JPEG Snapshot
	Resolution	50Hz Mode:720P(1280x720) / D1(704X576) / CIF(352X288)
		60Hz Mode: 720P(1280x720) / D1(704X480) / CIF(352X240)
	Frame Rate	Main Stream: 720P/D1(1 ~ 25/30fps), Sub stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 64K~4096Kbps	
Network	Ethernet	RJ-45 (10/100 Base-T)
	Protocols	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud
	ONVIF	ONVIF Ver. 2.0
	Max. User Access	10 users
	Smart Phone	iPhone,Windows Mobile, BlackBerry,Symbian, Android
	Browser	IE, Chrome, Firefox, Safari
General	Operating Condition	14 °F ~ 140 °F (-10°C~60°C), Humidity10%~ 90%
	Power Supply	DC12V, PoE (802.3af)
	Power Consumption	<6W
	Protection Range	IP66
	Dimension	3.94" x 3.27"
	Weight	0.99 lbs (450g)