




2 Megapixel IR Dome Camera

IV-DF362MP

Features:

- 1/3" 2Megapixel Aptina CMOS
- H.264 & JPEG dual-stream
- 1920 x 1080 / 15fps
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS
- 3.6mm fixed lens
- IR LEDs Distance 60ft
- Vandal Proof
- IP66
- DC 12V/ PoE



SPECIFICATIONS		IV-DF362MP				
Camera	Image Sensor	1/3" 2 Megapixel Aptina CMOS				
	Solution	TI DM368 + APTINA AR0130				
	Effective Pixels	1920 x 1080				
	Scanning System	Progressive				
	Electronic Shutter Speed	Auto/Manual 1/50~1/10000				
	Min. Illumination	Color: 0. 1LUX/F1.4, B/W: 0.01LUX/F1.4,0Lux (IR on)				
	S/N Ratio	>50dB				
Camera Features	Max. IR LEDs Length	60 feet				
	Day/Night	Auto(ICR) / Color / B/W				
	Backlight Compensation	BLC				
	White Balance	Auto				
	Gain Control	Auto/Manual				
	Noise Reduction	3D				
	Privacy Masking	Up to 4 areas				
	Slow Shutter	None / Low / Middle / High				
Motion Detection	22X18 areas					
Lens	Focal Length	3.6mm				
	Max Aperture	F1.2 (F1.8/F1.8)				
	Mount Type	Board-in Type				
Video	Compression	H.264 High Profile / JPEG Snapshot				
	Resolution	3.0M(2048x 1536)/1080P(1920x 1080) / 720P(1280x 720) / D1(704x 576/704x 480) /CIF(352x 288/352x 240)				
	Frame Rate	<table border="1"> <tr> <td>Main Stream</td> <td>2048x1536 (1~15 fps) 1920x1080,1600x1200,1280x960,1280x720(1~ 25/30 fps)</td> </tr> <tr> <td>Sub Stream</td> <td>640x360,480x270,352x288,320x240,352x192,320x192(1~25/30 fps)</td> </tr> </table>	Main Stream	2048x1536 (1~15 fps) 1920x1080,1600x1200,1280x960,1280x720(1~ 25/30 fps)	Sub Stream	640x360,480x270,352x288,320x240,352x192,320x192(1~25/30 fps)
	Main Stream	2048x1536 (1~15 fps) 1920x1080,1600x1200,1280x960,1280x720(1~ 25/30 fps)				
Sub Stream	640x360,480x270,352x288,320x240,352x192,320x192(1~25/30 fps)					
Bit Rate	H.264: 50K ~ 8192Kbps					
Network	Ethernet	RJ-45 (10/100Base-T)				
	Protocol	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud				
	ONVIF	ONVIF Ver. 2.0				
	Max. User Access	5 users				
	Smart Phone	iPhone, Android				
	Browser	IE				
General	Power Supply	DC12V / PoE				
	Power Consumption	<6W				
	Working Environment	Temperature: 14°F ~ 140°F, Humidity: 10%~90%				
	Ingress Protection	IP66				
	Dimensions	Ø 4" x 3" (H)				
	Weight	0.85 lbs				