



# 1.3 Megapixel IR Dome Camera

## IV-DP3613MP

### Features:

- 1/3" 1.3Megapixel Aptina CMOS
- H.264 & JPEG dual-stream
- 1280 x 960
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS
- 3.6mm fixed lens
- IR LEDs Distance 50ft
- Vandal Proof
- IP66
- DC 12V



SPECIFICATIONS		IV-DP3613MP	
Camera	Image Sensor	1/3" 1.3 Megapixel Aptina CMOS	
	Solution	TI DM368 + APTINA AR0330	
	Effective Pixels	1280 x 960	
	Scanning System	Progressive	
	Electronic Shutter Speed	Auto/Manual 1/50~1/10000	
	Min. Illumination	Color: 0. 1LUX/F1.4, B/W: 0.01LUX/F1.4,0Lux (IR on)	
	S/N Ratio	>50dB	
Camera Features	Max. IR LEDs Length	60 feet	
	Day/Night	Auto(ICR) / Color / B/W	
	Backlight Compensation	BLC	
	White Balance	Auto	
	Gain Control	Auto/Manual	
	Noise Reduction	3D	
	Privacy Masking	Up to 4 areas	
	Slow Shutter	None / Low / Middle / High	
Motion Detection	22X18 areas		
Lens	Focal Length	3.6mm	
	Max Aperture	F1.2 (F1.8/F1.8)	
	Mount Type	Board-in Type	
Video	Compression	H.264 High Profile / JPEG Snapshot	
	Resolution	1080P(1920x 1080) / 720P(1280x 720) / D1(704x 576/704x 480) /CIF(352x 288/352x 240)	
	Frame Rate	Main Stream	1920x1080,1600x1200,1280x960,1280x720(1~ 25/30 fps)
		Sub Stream	640x360,480x270,352x288,320x240,352x192,320x192(1~25/30 fps)
Bit Rate	H.264: 50K ~ 8192Kbps		
Network	Ethernet	RJ-45 (10/100Base-T)	
	Protocol	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud	
	ONVIF	ONVIF Ver. 2.0	
	Max. User Access	5 users	
	Smart Phone	iPhone, Android	
	Browser	IE	
General	Power Supply	DC12V / PoE	
	Power Consumption	<6W	
	Working Environment	Temperature: 14°F ~ 140°F, Humidity: 10%~90%	
	Ingress Protection	IP66	
	Dimensions	4.75" x 2.5"	
	Weight	10.58 oz	