



Vandal-proof IR Dome Camera

IV-DV409IRWDR

Features:

- . 1/3" SONY Ex-view HAD II CCD (960H)
- . Sony Effio-P
- . Color 700TVL
- . Color: 0.03Lux/F1.2, B/W: 0.00009Lux/F1.2 (sens-up on)
- . Electronic shutter adjustable, Mirror function, multi WB models
- WDR, NR(3D noise reduction), motion detection zoom in, Privacy zones, BLC
- HLC, CRR, Sens-up
- . OSD menu, 2.8-12mm varifocal lens, 3 Axis Mount, IR distance: 45~60ft, DC12V/AC24V



Specification	IV-DV409IRWDR
Pick-up device	1/3" SONY Ex-view HAD II CCD (960H)
Effective pixels	NTSC:976H*494V; PAL:976H*582V
Resolution	Color 700TVL
Min.illumination	Color: 0.03Lux/F1.2, B/W: 0.00009Lux/F1.2 (sens-up on)
Scan system	2:1 interlace
Sync system	Internal/Line lock
lens	2.8-12mm varifocal lens
IR Distance	45~60ft (,21XΦ5 leds)
Electronic shutter	AUTO(1/60~1/100,000) /FIXED/MANUAL
White balance	MANUAL/USER1/USER2/PUSH/PUSH LOCK/ANTI CR/ATW
NR	2D+3D noise reduction
Image adjustment	Brightness/Contrast/Sharpness/Hue/Gain
WDR	Low/Middle/High
BLC	HLC/BLC/OFF
AGC	ON/OFF
Day&Night	B/W/Color/Auto
Privacy zones	Off/On (15 areas)
Motion detection	Off/On (4 areas)
Mirror function	V-flip/H-flip/HV-Flip/OFF
Gamma	0.45 (Default)
S/N ratio	more than 52dB
Language	English/Chinese
Video output	1.0Vp-p Composite Video Output, 75 Ohm
Power supply	DC12V/AC24V
Power consumption(Max)	200mA/400mA(IR on) under DC12V
Operation temp	-4°F~140°F (-20°C ~ 60°C)