



Wireless N Router

IV-WR2416

Features:

- . Wireless N speed up to 300Mbps
- . 2*5dBi high gain antennas provide better signal coverage and reception
- . Fast setup the router and configure Repeater & Wireless with the Setup CD
- . Multi-wireless modes to expand the wireless network: AP, WDS, AP+WDS, Client, Repeater



SPECIFICATION	IV-WR2416
Wireless	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 300Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	20dBm(MAX)
Data Transfer Rate	802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps,9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	AP, WDS, AP+WDS, Repeater, Client, Multiple AP
Wireless Security	64/128-bit WEP, WPA-PSK/WPA2-PSK (TKIP/AES), SSID Broadcast Enable/Disable, Wireless MAC Filtering
Hardware	
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interface	1 * 10/100M Auto MDI/MDIX RJ45 WAN port ; 4 * 10/100M Auto MDI/MDIX RJ45 LAN port
LED	SYS,WPS, WAN, LAN1-LAN4
Button	Default, WPS
Antenna	2 * external 5dBi antennas
Power Supply	DC 9V/500mA(Output)
Dimensions (L x W x H)	6.73" x 4.21" x 1.10" (171 x 107 x 28mm)
Weight	0.408 lbs (185 g)
Software	
WAN Type	DHCP(Dynamic IP), PPPoE, Static IP, WISP
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port
QoS	WMM, Bandwidth Control
Access Control	IP/ MAC/Domain Filtering
VPN Pass-through	PPTP, L2TP, IPSEC
Others	DDNS, Static Routing, WOL, Remote Management, Firmware upgrade
Others	
Certification	FCC, CE, KC, NCC, BSMI
Environment	Operating Temperature: 32°F~104°F (0°C~40°C); Storage Temperature: -40°F~158°F (-40°C~70°C) Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
Package	1* WR2416, 1* Quick Installation Guide, 1* Setup CD 1* Power Adapter, 1* Ethernet Cable