





6MP IP Fisheye Camera

IV-SN6MP360FE

Features:

- . 1/1.8" Progressive Scan CMOS
- . 6MP Resolution
- . Memory card slot for Micro SD / SDHC
- . 3D DNR DWDR, ICR, True Day/ Night
- . IR distance 30ft
- . DC 12V/ PoE
- . IP66



IV-PCK636WM
(Optional)

Specification	IV-SN6MP360FE
Sensor	1/1.8" Progressive Scan CMOS
Max Res./ Max Frame Rate	3072(H)*2048(V)/30fp with Fisheye correction
Min. Illumination	0.01 Lux (Color) (0.01Lux B/W) (0 Lux IR LED On) camera
CAMERA	
Day / Night	True Day / Night with ICR Filter
Lens	360° Fisheye F1.6
Field of View (H / V / D)	77° / 54° / 100.2°
IR LED	High Powered Super Flux LEDs 850nm
IR Distance	30 ft / 10 Meters
Video Output	Setup / Service BNC Video supported internal connector with dangle cable supplied
Electronic Shutter	Auto / User 1/5 - 1/50,000 ; 50/60Hz software selectable video
VIDEO	
Compression	H-264 High/Main/Base Profile. Stream1 H-264, or MJPEG.
Streaming	Stream1 Full Resolution, Stream2 VGA / D1 / CIF or QCIF selectable
Quality Setting (VBR)	1 - 9 (9 Highest)
I Frame	User selection value
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102dB
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas network
Network Protocols:	
Ethernet	1 Ethernet (10/100 Base-T) RJ45 Connector
TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 (Profile S)
RTSP Video	Standard RFC2326, Support Quick time / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish
Recording Simultaneous.	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection
Network Protocols:	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPPoE, NTP. Unicast and Multicast supported Video streaming from SDK & NVMS / NVR software or 3rd party applications. AUDIO
Input / Output	Optional Microphone: 1 x RCA Input / 1 x RCA Output @ 1V Line Level
Audio Compression	G711 A-law, G711 u-law , RAW_PCM
GENERAL	
Power	12V DC Terminal Input / PoE 802.3af Class 2 4.1W / Max 6.9W (LED On)
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
Approval	UL / CE / FCC / RoHS Compliant / IK10
Dimensions	3.15" x 2.1" / 80 x 54 mm