



## 8CH 960P Plug & Play WIFI NVR Kit

### Wireless 960P NVR Kit



**IV-K808BU13MP-WIFI**

**Features:**

- . HD video output
- . Automatic connection with IP, save installation cost
- . Plug and play, P2P service
- . Mobile viewing, iphone&android app
- . Free DDNS: [www.e-seenet.com](http://www.e-seenet.com), no need DDNS setting
- . Once connected to Power, camera connect to NVR automatically
- . Wireless signal transmission distance 330 feet in open area (no obstacles)
- . Wireless signal transimission distance around 90 feet with obstacles (depend on obstacles)

**Package includes:**

- . 8pcs 960P camera
- . 1pcs 8ch 960P NVR
- . 1pcs network cable
- . 1pcs12V 3A+8pcs 12V 1A power supply
- . English User Manual
- . Mouse
- . 1 pcs 4-port USB Hub

Specification	IV-K808BU13MP-WIFI	
<b>Wireless NVR Specification</b>		
	Operating System	Embedded Linux OS
AV(audio/video)input	Network Video	8CH
	Network video input broadband	20Mbps
	Audio Bitrate	64Kbps
AV (audio/video) output	HDMI output	1ch, resolution: 1024x768, 1366x768, 1440x900,1920x1080p
AV CODEC Specification	Video Resolution	D1/720P/960P
	synch-playback	8CH
Video Control	Video/Capture mode	Manual、Time、Motion
	Playback mode	Real time、Routine、Event
	Backup	USB backup
Hard Disk	Type	1*SATA interface
	Max Capacity	4 TB at most for each
External Interface	Network Interface	4 adaptable RJ45 10M/100M, 2 WIFI interface
	USB Interface	1 USB 2.0 (with a USB Hub for extension)
Network Control	Protocol	UPnP(play&plug)/SMTP(email service)/PPPoE (dial-up)/ DHCP (Automatically obtain an IP address), etc.
Others	Power Supply	DC12V 2A
	Power Consumption (W)	≤5W(Without HDD)
	Operate Temperature (°C)	14°F ~ 131°F / -10°C~+55°C
	Working Humidity (%) RH	10%~90%
	Size	10.1" x 8.27" x 1.77" / 257mm(W)×210mm(V)×45mm(H)
	Weight(excluding HDD)	≤ 2.20lbs / 1Kg
<b>IPC Specification</b>		
Technical Parameters	Sensor	1/3" Progressive Scan Sensor
	Signal System	PAL/NTSC
	Resolution	1280 x 960, 16 : 9 High Definition
	Minimum illumination	Color: 0.1 Lux; B/W: 0.01 Lux
	Shutter	1/25s to 1/25,000s
	Lens	3.6mm
	OSD	Date Time&Title
	White Balance	Auto
	Day&Night	Auto/Color/BW
	3D-DNR	Auto
	Mirror/Flip	On/Off
	Frame Specification	Dual Streaming at the Same Time: H.264 1280 x 960@15 fps or below; H.264 640 x 360@15fps or below
	S/N	> 39.1 Db
Interface	RJ45/WIFI 802.11b/g/n	
General Specification	Anti-thunder Level	Standard IEC61000-4-5
	Working Temperature/Humidity	14°F ~ 122°F / -10°C to+50°C/30% to 80% RH
	Working Temperature/Humidity	-4°F ~ 140°F / -20°C to+60°C/20% to 90% RH
	Power Input	DC12V-1A
	Power consumption	≤6W
	Size	8.07" x 2.75" x 2.16" / 205(L)×70(W)×55 (H)mm
	Weight	1.10 lbs / 500g
Ingress Protection	IP66	
<b>IDView Technologies • 12000 Ford Rd. Suite 110 • Dallas, TX 75234 • www.digitalidview.com</b>		