



1.3 Megapixel IR Bullet Camera

IV-BUF3613MP

Features:

- . 1/3" Aptina CMOS
- . HD 720P
- . 0.1Lux @(F1.4,AGC ON), 0Lux with IR
- . H.264 high profile compression
- . IR-CUT filter switch
- . Dual stream, 3-Axis
- . Support electronic shutter
- . ONVIF 2.0



Specification	IV-BUF3613MP
Camera	
Image Sensor	1/3" 1.3 Megapixel Aptina CMOS
Effective Pixels	1280 x 960
Scanning System	Progressive
Min. Illumination	Color:0.1Lux / F1.4
	B/W:0.01 Lux / F1.4, 0 Lux (IR on)
Electronic Shutter	Auto / Manual 1/50 ~ 1/10,000
Day & Night	Auto (ICR) / Color / B/W
S/N Ratio	> 50dB
Backlight Compensation	BLC
White Balance	Auto
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 Areas
IR distance	45~60 ft
Slow Shutter	None /Low/ Middle/ High
Motion Detection	22X18 area
Lens	
Focal Lens	3.6mm / F1.2 / Angle of View H:70°
Mount Type	Board-in Type
Video	
Compression	H.264 Main Profile, JPEG Snapshot
Resolution	50Hz Mode:720P(1280x720) / D1(704X576) / CIF(352X288)
	60Hz Mode: 720P(1280x720) / D1(704X480) / CIF(352X240)
Frame Rate	Main Stream: 720P/D1(1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 64K~4096Kbps
Network	
Ethernet	RJ-45 (10/100 Base-T)
Protocols	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud
ONVIF	ONVIF Ver. 2.0
Max. User Access	10 users
Smart Phone	iPhone,Windows Mobile, BlackBerry,Symbian, Android
Browser	IE、Chrome、Firefox、Safari
General	
Operating Condition	-14 °F ~ 140 °F (-25°C~60°C), Humidity10%~ 90%
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<6W
Protection Range	IP66
Dimension	6.28" x 2.93"
Weight	1.10 lbs (500g)