



## Client Server

### IV-Client Server

#### Features:

- . Software Independent Platform
- . Hardware exceeds minimum requirements
- . Preconfigured to auto connect to cameras
- . Configured to provide desired camera layout
- . Utilizes low heat 2.5" hard drives
- . Can be used in horizontal and vertical position
- . USB ports in the front for easy download or snapshots
- . Slimline DVDRW for archiving of files
- . Easily bring cameras up to full screen and zoom in on regions of interest
- . Supports auto sequencing
- . View 4 to 32 cameras (CPU dependent)
- . eSata port on front can be used for video archiving
- . Lower power consumption than standard PCs



SPECIFICATION	IV-Client Server
<b>CPU</b>	i3 / i5 / i7
<b>RAM</b>	Minimum of 1GB
<b>NIC Card</b>	10 / 100 / 1000
<b>Display</b>	1920 x 1200 (2560 x 1600 with optional adapter)
<b>Keyboard &amp; Mouse</b>	Included, not required for Cameras to be viewd
<b>Operating System</b>	Windows 7
<b>Audio Connectors</b>	Microphone and Speaker
<b>Hard Drives</b>	250GB minimum can be upgraded to 2 TB max.
<b>Connectors</b>	USB 2 x 2.0 on front 2 x 2.0 on back
	RJ-45
	1 HDMI, 1 Display Port
	Front eSATA port
	DC 12V
<b>Regulatory</b>	CE (Class A), FCC (Class A), UL-Listed
<b>Warranty</b>	1 Year Basic Service Plan (Upgradable to max 5 years)
<b>Power</b>	150W
<b>Weight</b>	< 8 lb
<b>Temperature</b>	5°C~ 45°C / 41°F ~ 113°F
<b>Humidity</b>	5% ~ 90% (non condensing)
<b>Size</b>	4 x 7 x 12 inches

