



IP Camera -Server 2

IV-Server-2

Features:

- . Software Independent Platform
- . Hardware exceeds minimum requirements
- . Powerful CPU
- . Flexible hard drive configurations
- . Multiple Case Choices
- . Rack Mountable case available
- . Optional RAID configuration available
- . Multiple Video Management Software available
- . Many VMS will support Network attached Storage
- . Optional Cooling Upgrades available
- . Many VMS will support Network attached Storage
- . Software can be configured to run as a service
- . Optional Multi Monitor Support
- . DVDRW for video archiving
- . Front USB port for easy flash drive backup and system upgrades
- . IP Address of cameras can be preconfigured
- . Up to 16 2MP cameras with eView software
- . Up to 8 2MP cameras with VI software

Customized case available on request



SPECIFICATION	IV-Server-2
CPU	I5
RAM	Minimum of 2GB
Video Quad Card	GeForce 6200 4 VGA outputs 512MB DDR2
Ethernet	10 / 100 / 1000 baseT, full-duplex
Display	Intel 9459 Express chip set
Hard Drives	Case Dependent, Up to 12TB internal storage
Connectors	USB 1.x/2.0 x 2
	RJ-45
	VGA DSB 15 pins
	DC 12V
Power	AC 110V / 300Watt up
Weight	35 lbs
Temperature	5°C~ 45°C / 41°F ~ 113°F
Humidity	5% ~ 90% (non condensing)
Safety	FCC Class B/CE/UL