



Anti-Corrosion Stainless Steel Housing with Wiper & IR

Anti-Corrosion Stainless Steel Housing with Wiper & IR IV-OH-ATCS316IR-Wiper



Features:

- . Degree of protection provided by enclosures (IP Code) IP 68
- . The cable entry and cable glands can be customized to meet the customer's requirement
- . Monitoring complete view of all areas, it is applicable for Oil Gas Refineries, Chemical Plants, Metal Plating Plants, Production Plants, and Various Industries
- . The Stainless Steel housing can accommodate standard cameras and lens
- . Magnetic post can be adjust the zoom/focus (in case of analog camera)
- . Infrared illuminator is with 150ft (50 Meters) projecting distance



3/4" : IV-CGS34-ATEX 1/2" : IV-CGS21-ATEX
Anti-Corrosion Cable Glands (optional)



Wall Mount IV-WM5011-ATEX (optional)

Specification	IV-OH-ATCS316IR-Wiper
Construction	Stainless Steel Construction SUS304/SUS316 to guarantee max. corrosion resistance
Window	Ø 65 mm and 10 mm High-Density Toughened Glass
Internal Dimension	70 mm x 70 mm
Finish	Electro-Polished / Paint Coating / Electrolytic Plating / Powder Coating
Water-proof Standard	Adopted International Standard CNS3376-0/IP68
Wiper Material	Stainless Steel Construction SUS304/SUS316 to guarantee max. corrosion resistance
Wiper Dimension	55 mm in Length
Wiper Blades	Rubber Material (IV-OH-ATEX316IR-Wiper) optional
Sunshield	Stainless Steel to guarantee max. corrosion resistance
External Interface	Standard 1/2" or 3/4" Connection
IR Projection Distance	150ft (50 Meters) with 18 High Power IR LED Lights
Operation Environment	Applicable in High Temperature, Chemical, Corrosive Environments, and Oil Refineries or Salt Refineries, etc.
Dimension of Appearance	12.87" x 5.2" x 5.2" (327 (L) x 132 (W) x 132 (H) mm)
Optional	Stainless Steel Bracket IV-WM336-ATEX
Optional	Anti-corrosion cable glands 1/2" or 3/4"
Optional	Camera specifications features to be custom made per each project