



5 MP IR Day/Night Weatherproof Bullet Camera

GS-AH5585P

Features:

- 5 Megapixel 2592 x 1944 Pixels
- Sony Exmor CMOS 1/1.8" Sensor
- H265, H264, and MJPEG Encoding.
- 22 Pieces IR LEDs (40-60ft Illumination Max)
- WDR (Wide Dynamic Range)
- IP66 Weatherproof Bullet
- 3.6-10mm Varifocal Motorized P-Iris Lens
- Onvif Compliant
- 2 Way Audio



Specification		GS-AH5585P
Camera	Image Sensor	1/1.8" Sony Exmor 5 Megapixel Image Sensor
	Effective Pixels	2592x1944
	Scanning System	Progressive
	Min. Illumination	Color: 0.1 l B/W: 0 lux (IR LED on)
	Electronic Shutter	Auto / Manual 1/50 - 1/10,000
	Day & Night	Auto (ICR) / Color / B/W
	S/N Ratio	> 52dB
	IR distance	90 feet
	Backlight Compensation	BLC
	White Balance	Auto
	Gain Control	Auto / Manual
	Noise Reduction	3D
	Privacy Masking	Up to 4 Areas
	Slow Shutter	None /Low/ Middle/ High
Motion Detection	10-Zone Video Motion Detection	
Lens	Focal Lens	3.6-10mm Motorized Varifocal P-Iris Megapixel Lens
	Mount Type	Board-in Type
Video	Compression	H265, H.264 (Hi Profile and Baseline) , MJPEG
	Resolution	50Hz Mode:5MP (2592x1944), Max 20fps
		60Hz Mode: 5MP (2592x1944), Max 20fps
	Frame Rate	Main Stream: 5MP(1 ~ 25/30fps), Sub stream: 4MP(1 ~ 25/30fps)
Bit Rate	H.264: 64K~4096Kbps	
Network	Ethernet	RJ-45 (10/100 Base-T)
	Protocols	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud
	ONVIF	ONVIF Ver. 2.0
	Max. User Access	10 users
	Smart Phone	iPhone,Windows Mobile, BlackBerry,Symbian, Android
	Browser	IE, Chrome, Firefox, Safari
General	Operating Condition	14 °F ~ 140 °F (-10°C~60°C), Humidity10%~ 90%
	Power Supply	DC12V, PoE (802.3af)
	Power Consumption	<6W
	Protection Range	IP66
	Dimension	10" Length 2.75" Diameter
	Weight	0.99 lbs (450g)