



32CH 4K H.265 Network Video Recorder

IV-MX32POENVR5MP

- Save 50% storage & bandwidth
- Standalone Linux embedded system
- Web-based management
- 5MP Video input/output
- 32 CH (32 through external LAN switch)
- Max. 7 x SATA Devices
- Support H.264 / H.265
- ONVIF 2.4
- Support touch monitor



Specification		IV-MX32POENVR5MP	
Camera Input		32 CH (32 through external LAN switch)	
Video	Input	32CH 5MP	
	Output	Max. 2560 x 1944 1 HDMI with Audio and 1 VGA	
Audio	Output	1	
Display	Split Screen	1, 4, 9, 13, 16, 25, 32 SEQ.	
	Auto Channel Switching	Switching time : 1 - 99 sec	
	Mode	Zoom, PIP, Auto SEQ.	
Recording	Recording Throughput (60Hz / 50Hz IP Camera)	Support H.264 / H.265 1280 * 720 @ 30/25 fps 1920 * 1080 @ 30/25 fps 2560 * 1944 @ 30/25 fps Bitrate <10Mbps / per CH ; Total bitrate < 220Mbps	
	Mode	Continuous, Event, Schedule	
Playback	Search Mode	Date / Time, Event	
	Zoom	*Digital (x2 - x5)	
Network	Network Interface	10/100/1000 Ethernet	
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS, FTP	
	ONVIF	Onvif 2.4	
	Remote Software	iWatch DVR, IE Browser, iCMS Pro	
	Account	1 Admin + 10 Users	
	Mobile Device	iPhone, iPad, Android	
Backup	Interface	USB 2.0	
	Audio Backup	YES	
	Backup Type	Network, Ext. USB flash device , SATA optical DVD..etc	
Alarm	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)	
OSD & DVR Control	Multi-Language	Supported	
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)	
	System Upgrade	USB Flash Drive, iWatch DVR	
	Operating System	Embedded Linux OS	
System	SATA Devices	Max. 7 x SATA Devices (HDDx7+eSATAx1, HDDx1+ Optical Devicex1+eSATAx1)	
	External HDD	YES (eSATA)	
	USB 2.0 Ports	USB 2.0 x2 , USB 3.0 x1	
	Dimension	16.93" x 2.17" x 11.54"	
	Net Weight	7.72 lbs	
	Power Rating		DC 12V 5A 60W
			Adapter 110/220V
General	Operating Temperature	32°F ~ 131°F	
	Operating Humidity	10%~90%	