



2 MP Ultra Miniature IP Pinhole Camera

IV-PHPoE3.7

Features:

- . 1/2.8" Progressive Scan CMOS
- . 3.7mm Pinhole lens
- . 2MP, 1920 x 1080
- . Multiple Streams
- . DV 12V / PoE
- . ROI, HLC, Defog, Corridor Mode



SPECIFICATION	IV-PHPoE3.7
Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	Color: 0.05Lux(AGC ON); B&W: 0.01Lux(AGC ON)
Day & Night	Fixed
Shutter Speed	1/5-1/20000
Auto Iris	Fixed
Digital Noise Reduction	3D
Lens	3.7mm Pinhole
FOV	84°
Video Compression	H.265/H.264/MJPEG
Bit Rate (CBR/VBR)	Main stream: 500Kb-12000Kb / Sub stream: 200Kb-8000Kb
Max.Resolution	1920x1080/30fps
Stream	Stream1 1920x1080 / 1280x720; Stream2 D1/VGA/640x360/CIF /QVGA
Image Setting	Rotate Mode, Saturation, Brightness ,Contrast ,Sharpness
HLC	Auto
9:16 Corrido mode	Yes
ROI / Defog	Yes
Network Protocols	IPv4,802.1x,HTTP,HTTPS,TCP/IP,UDP/IP,RTSP,DHCP,NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, ICMP ,IGMP, Unicast and Multicast
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player.
Security	User security authentication, Reset, Hardware Watch Dog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish.(Sunell Brand)
System Compatibility	Onvif
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Power Supply	DC12V
Power Consumption	3W(MAX)
OperatingTemperature	Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) / Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F)
Operating Humidity	0% - 90% RH
Dimensions	37.6x32.8x46.5mm
Weight	180g